

SE Series

Explosion-proof Spring Return Fail-safe Electric Valve Actuator

Electrical Data



INDEX

1.	SE-500 to 2600, 1PH, 50% duty cycle	1
1.1	24VAC/DC, ON/OFF Control, 50% duty cycle	1
1.2	110-120VAC, ON/OFF, Floating or Modulating Control, 50% duty cycle	1
1.3	220-240VAC, ON/OFF, Floating or Modulating Control, 50% duty cycle	1
2.	SE-500 to 2600, 3PH, 50% duty cycle	2
2.1	220-240VAC, ON/OFF Control, 50% duty cycle	2
2.2	380-415VAC, ON/OFF Control, 50% duty cycle	2
2.3	440-480VAC, ON/OFF Control, 50% duty cycle	2

1. SE-500 to 2600, 1PH, 50% duty cycle

1.1 24VAC/DC, ON/OFF Control, 50% duty cycle

Model	Torque		Motor Power	Running Current	Running Time	Return Time	Lock Current
	N·m	in·lb		DC / 60 / 50Hz	DC / 60 / 50Hz		DC / 60 / 50Hz
			Watt	Amp	Sec / 90°	Sec / 90°	Amp
SE-500	50	445	50	3.4 / 4.2 / 4.1	7 / 7 / 9	3	12.0 / 10.4 / 10.0
SE-1300	130	1150	130	7.3 / 10.0 / 10.1	8 / 7 / 8	8	20.5 / 17.5 / 17.2
SE-2000	200	1770	130	6.3 / 8.6 / 8.6	11 / 11 / 13	12	20.9 / 17.6 / 17.3
SE-2600	260	2300	130	7.3 / 10.2 / 10.2	17 / 14 / 17	12	20.9 / 17.6 / 17.3

1.2 110-120VAC, ON/OFF, Floating or Modulating Control, 50% duty cycle

Model	Torque		Motor Power	Running Current	Running Time	Return Time	Lock Current
	N·m	in·lb		60 / 50Hz	60 / 50Hz		60 / 50Hz
			Watt	Amp	Sec / 90°	Sec / 90°	Amp
SE-500	50	445	50	1.2 / 1.5	7 / 9	3	1.6 / 1.9
SE-1300	130	1150	130	4.3 / 7.2	7 / 8	8	11.5 / 12.0
SE-2000	200	1770	130	4.9 / 7.7	11 / 13	12	11.6 / 12.6
SE-2600	260	2300	130	4.0 / 7.3	14 / 17	12	11.6 / 12.6

1.3 220-240VAC, ON/OFF, Floating or Modulating Control, 50% duty cycle

Model	Torque		Motor Power	Running Current	Running Time	Return Time	Lock Current
	N·m	in·lb		60 / 50Hz	60 / 50Hz		60 / 50Hz
			Watt	Amp	Sec / 90°	Sec / 90°	Amp
SE-500	50	445	50	0.8 / 0.8	7 / 9	3	0.8 / 0.9
SE-1300	130	1150	130	2.1 / 3.6	7 / 8	8	5.5 / 6.0
SE-2000	200	1770	130	2.2 / 3.8	11 / 13	12	5.9 / 6.2
SE-2600	260	2300	130	2.5 / 3.8	14 / 17	12	5.9 / 6.2

2. SE-500 to 2600, 3PH, 50% duty cycle

2.1 220-240VAC, ON/OFF Control, 50% duty cycle

Model	Torque		Motor Power	Running Current	Running Time	Return Time	Lock Current
	N·m	in·lb		60 / 50Hz	60 / 50Hz		60 / 50Hz
			Watt	Amp	Sec / 90°	Sec / 90°	Amp
SE-500	50	443	50	0.8 / 0.8	7 / 9	3	0.8 / 0.9
SE-1300	130	1151	130	2.1 / 3.6	7 / 8	8	5.5 / 6.0
SE-2000	200	1771	130	2.2 / 3.8	11 / 13	12	5.9 / 6.2
SE-2600	260	2302	130	2.5 / 3.8	14 / 17	12	5.9 / 6.2

2.2 380-415VAC, ON/OFF Control, 50% duty cycle

Model	Torque		Motor Power	Running Current	Running Time	Return Time	Lock Current
	N·m	in·lb		60 / 50Hz	60 / 50Hz		60 / 50Hz
			Watt	Amp	Sec / 90°	Sec / 90°	Amp
SE-500	50	443	50	0.5 / 0.6	7 / 9	3	0.5 / 0.7
SE-1300	130	1151	130	1.3 / 1.7	7 / 8	8	2.6 / 2.7
SE-2000	200	1771	130	0.8 / 1.0	11 / 13	12	1.9 / 2.0
SE-2600	260	2302	130	0.8 / 1.1	14 / 17	12	1.9 / 2.0

2.3 440-480VAC, ON/OFF Control, 50% duty cycle

Model	Torque		Motor Power	Running Current	Running Time	Return Time	Lock Current
	N·m	in·lb		60 / 50Hz	60 / 50Hz		60 / 50Hz
			Watt	Amp	Sec / 90°	Sec / 90°	Amp
SE-500	50	443	50	0.3 / 0.4	7 / 9	3	0.4 / 0.5
SE-1300	130	1151	130	0.9 / 1.3	7 / 8	8	2.2 / 2.3
SE-2000	200	1771	130	0.9 / 1.4	11 / 13	12	2.2 / 2.2
SE-2600	260	2302	130	0.9 / 1.2	14 / 17	12	2.2 / 2.2